

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

- 1                   1.       (Previously presented): An external storage system comprising:  
2                   a plurality of disk drives for storing data;  
3                   a drive interface control unit operatively couple to the disk drives;  
4                   a channel interface control unit through which a connection with a supervisory  
5 unit can be established for reading and writing data;  
6                   a cache memory connected to the drive interface control unit and to the channel  
7 interface control unit, the cache memory for temporarily storing data between the disk interface  
8 control unit and the channel interface control unit; and  
9                   a shared memory connected to the drive interface control unit and to the channel  
10 interface control unit, the shared memory for storing information relating to data that is to be  
11 staged to the cache memory,  
12                   the information being used by the channel interface control unit to stage data that  
13 is stored in a plurality of tracks in one or more of the disk drives to the cache memory by way of  
14 the drive interface control unit,  
15                   the information further being used by the channel interface control unit to destage  
16 data from the cache memory to be stored to the disk drives by way of the drive interface control  
17 unit,  
18                   wherein staging of the data to the cache memory and destaging of the data from  
19 the cache memory are performed according to staging and destaging instructions from the  
20 supervisory unit, the instructions formulated by the supervisory unit according to criteria  
21 provided by a user.
2.       (Canceled)

1                   3.       (Previously presented): The external storage system as claimed in claim 1,  
2   in which the staging in or destaging from the cache memory of the user data is executed in a  
3   processing unit of a data-set domain.

1                   4.       (Currently amended): The external storage system as claimed in claim  
2   [2]1, in which the ~~storage instaging or removal from the cache memory~~destaging of the user data  
3   is ~~executed in a processing unit of~~are performed for a data-set domain.

1                   5.       (Previously presented): An information processing system having an  
2   external storage system and a host unit which is external to the external storage system and  
3   connected to the external storage system, in which the external storage system comprises a  
4   plurality of disk drives, a drive interface control unit, a channel interface control unit, a shared  
5   memory, and a cache memory, in which the host unit executes writing and reading data to the  
6   external storage system, and in which  
7                   the host unit has a host utility program to manage data in the cache memory, and  
8   user defined information or operating information of the external storage system for execution of  
9   the host utility program,

10                  wherein the host utility program can issue a resident command to instruct the  
11   channel interface control unit to set residing data in the cache memory, and can issue a reset  
12   command to instruct the channel interface control unit to reset residing data in the cache  
13   memory,

14                  wherein the channel interface unit in the external storage system receives the  
15   resident command and the reset command based on the user defined information or the operating  
16   information,

17                  wherein the drive interface control unit is operable to store data on the disk drives,  
18                  wherein the cache memory is in data communication with the drive interface  
19   control unit and the channel interface control unit,

20                    wherein the shared memory is in data communication with the drive interface  
21 control unit and the channel interface control unit, and stores first information relating to data  
22 stored in the cache memory,  
23                    wherein the channel interface control unit sets and resets residing data in the  
24 cache based on the first information.

1                    6.        (Currently amended): The information processing system as claimed in  
2 claim ~~[4]~~5, in which the ~~storage of a set of user data~~residing data is set or reset in the cache  
3 memory ~~or removal of the user data from the cache memory is executed in a~~in units of data-set  
4 domains.

1                    7.        (Currently amended): The ~~information processing external storage~~ system  
2 as claimed in claim ~~[4]~~1, in which the ~~user defined~~ information includes a data-set name which is  
3 entered by a user~~from a terminal connected to the host computer~~.

1                    8.        (Original): The information processing system as claimed in claim 5, in  
2 which the user defined information includes a data-set name which is entered from a terminal  
3 connected to the host unit.

1                    9.        (Previously presented): A system comprising a host unit and a disk array  
2 system separate from the host unit and in data communication therewith, the disk array system  
3 comprising:  
4                    a plurality of disk drives for storing data;  
5                    a drive interface control unit operably coupled to the disk drives for transfer of  
6 data therewith;  
7                    a channel interface control unit to receive data transfer commands from a host  
8 unit;  
9                    a cache memory in data communication with channel interface control unit and  
10 with the drive interface control unit; and

11                   a shared memory in data communication with channel interface control unit and  
12   with the drive interface control unit, the shared memory having stored therein first information  
13   relating to data staged in the cache,  
14                   wherein the host unit can issue a resident command and a reset command;  
15                   wherein in response to receiving a resident command from the host unit, the  
16   channel interface control unit accesses the first information to store data received from disk  
17   drives into the cache memory,  
18                   wherein in response to receiving a reset command from the host unit, the channel  
19   interface control unit accesses the first information to reset data that is stored in the cache  
20   memory.

1                   10.   (New): The system as claimed in claim 9, in which the data is a data-set  
2   domain.

1                   11.   (New): The system as claimed in claim 9, in which the first information  
2   includes a data-set name that is provided by a user.